




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification<sup>6</sup> : <b>F25D 13/06, A23L 3/36</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 98/49505</b></p> <p>(43) International Publication Date: <b>5 November 1998 (05.11.98)</b></p>
<p>(21) International Application Number: <b>PCT/SE98/00735</b></p> <p>(22) International Filing Date: <b>23 April 1998 (23.04.98)</b></p> <p>(30) Priority Data: <b>9701550-7</b>      <b>25 April 1997 (25.04.97)</b>      <b>SE</b></p> <p>(71) Applicant (for all designated States except US): <b>FRIGOSCANDIA EQUIPMENT AB [SE/SE]; P.O. Box 913, S-251 09 Helsingborg (SE).</b></p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): <b>MALMBERG, Jonny [SE/SE]; Nedre Holländaregatan 28, S-252 26 Helsingborg (SE). OLSSON, Lennart [SE/SE]; Brovägen 21, S-260 41 Nyhamnsläge (SE).</b></p> <p>(74) Agent: <b>AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).</b></p>		<p>(81) Designated States: <b>AU, CA, CN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b></p> <p><b>Published</b> <i>With international search report.</i> <i>In English translation (filed in Swedish).</i></p>

(54) Title: **METHOD AND APPARATUS FOR SURFACE FREEZING**



(57) Abstract

In a method of freezing a surface layer of a food product (6), this is placed on a non-foam conveyor belt (7). Cold air in the form of jets is blown towards the underside of the non-foam conveyor belt. An apparatus for carrying out the method comprises, in addition to the non-foam conveyor belt (7), a plurality of stationary nozzles (14) for producing jets towards the underside of the non-foam conveyor belt in an area which extends over the width of the non-foam conveyor belt.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND APPARATUS FOR SURFACE FREEZING

The present invention relates to a method and an apparatus for freezing a surface layer of a food product.

When freezing products that do not have a fully solid structure, the products can easily mould to the base, on which they are frozen. This is disadvantageous if the base has a shape that differs from the one that is desirable for the product in its final frozen form. There is also a risk that the products freeze onto the base, which results on the one hand in the product being defective and, on the other hand, in residues of the product remaining on the base and needing to be removed before the base can be used again.

It is known that freezing fast can be avoided if the base is given a very low temperature. This is, however, a relatively energy-consuming method as it requires liquid nitrogen or the like. Alternatively, a foil can be used between the base and the product, in which case the product need not have such a low temperature. However, the heat transmission will then be relatively poor especially if the product is not so soft that a major part of its lower surface presses the foil into direct contact with the base.

The object of the present invention is to provide a method of freezing a surface layer of a food product in an energy-effective manner and while ensuring that the surface layer over the major part of the lower surface of the product is frozen.

According to the invention, this object is achieved by the method and the apparatus being given the distinguishing features that are evident from the appended independent method claim and apparatus claim, respectively. Various embodiments will appear from the dependent claims.

In the inventive method, the food product is thus placed on a non-foraminous conveyor belt and cold air

in the form of jets is blown towards the underside of the conveyor belt. This results in very efficient cooling of the non-foraminous conveyor belt from the underside thereof, thereby achieving rapid freezing of a layer  
5 closest to the lower surface of the product, said lower surface abutting directly against the upper side of the non-foraminous conveyor belt.

To freeze food products by subjecting them directly to cold jets is previously known, but many products of  
10 a wholly or partly looser consistency can, of course, probably not be subjected to such jets. By using a non-foraminous conveyor belt, it will however be possible to freeze also such food products at least over a surface in direct contact with the conveyor belt if the jets are  
15 instead directed to the underside of the conveyor belt and this is not made too thick or too poorly thermally conductive.

In a preferred embodiment, the non-foraminous conveyor belt comprises a non-foraminous foil strip supported by a foraminous supporting belt. When the cold jets  
20 are blown towards the underside of the this conveyor belt, they pass through the foraminous supporting belt and press the foil strip into intimate contact with a major part of the underside of the food product, even if  
25 this surface is somewhat uneven. Excellent heat transmission is thus achieved, and the bottom layer of the food product can rapidly be transferred to a frozen state.

In an alternative embodiment, the conveyor belt comprises a single belt of metal or some other material having good thermal conductivity, such that also in this  
30 case excellent heat transmission can be achieved and the bottom layer of the food product thus can be quickly transferred to a frozen state.

Preferably, the cold air is blown in the form of  
35 jets towards the underside of the non-foraminous conveyor belt in a stationary area, which extends over the width of the non-foraminous conveyor belt, while at the same

time the non-foraminous conveyor belt is successively moved past the stationary area.

In one embodiment, use is also made of a superposed, non-foraminous cover belt, which is positioned on top of and in contact with the food product on the non-foraminous conveyor belt and which is moved in parallel therewith. Also in this case, cold air is blown in the form of jets towards the upper side of the superposed cover belt. As a result, the entire surface layer, or a great part thereof, of the food product can be frozen effectively, i.e. with good heat transmission and in a short time.

An apparatus for carrying out the inventive method comprises a non-foraminous conveyor belt and a plurality of stationary nozzles for blowing cold air in the form of jets towards the underside of the non-foraminous conveyor belt in an area which extends over the width of the non-foraminous conveyor belt.

In a preferred embodiment, the non-foraminous conveyor belt comprises a non-foraminous foil strip supported by a foraminous supporting belt.

Alternatively, the non-foraminous conveyor belt can consist of a single non-foraminous belt of metal or some other material with good thermal conductivity.

In one embodiment, the apparatus also comprises a superposed, non-foraminous cover belt, which is arranged above the non-foraminous conveyor belt to cover a food product positioned on said conveyor belt, and a plurality of additional stationary nozzles for blowing cold air in the form of jets towards the upper side of the superposed, non-foraminous cover belt.

The superposed cover belt preferably is a non-foraminous foil strip, but it can also consist of a belt of metal or some other material with good thermal conductivity.

An embodiment of the invention will now be described in more detail with reference to the accompanying drawing

which is a schematic side view of a freezing apparatus for food products.

More specifically, the drawing illustrates a freezer 1 with a feed opening 2 and a discharge opening 3. The freezer 1 can be of the type using a foraminous conveyor belt 4, which moves the food products that are to be frozen along a helical path from the feed opening 2 to the discharge opening 3 while cold air is forced to flow round the food products, such that they are completely frozen when reaching the discharge opening 3 of the freezer 1.

An apparatus 5 according to the invention is in this case used as a prefreezer for producing at least a frozen bottom layer on food products 6 before they are placed on the foraminous conveyor belt 4 of the freezer 1.

The apparatus 5 comprises a foraminous supporting belt 5 which travels in an endless path over two deflecting rollers 8 and 9. A storage roll 10 contains a foil strip 11, which from the storage roll 10 is extended over an upper run 12 for the supporting belt 7 to a receiving roll 13.

Under the supporting belt 7 in the upper run 12 thereof, a plurality of stationary nozzles 14 are arranged. The nozzles 14 are distributed in an area which extends over essentially the entire width of the supporting belt 7, said width being essentially the same as or greater than the width of the foil strip 11. The nozzles 14 constitute outlets from a duct 15 which in turn is supplied with cold air at high pressure by means of a fan 16, such that the nozzles 14 eject jets, i.e. streams of air at such a speed that the layer of air closest to the foil strip 11 is broken, which considerably improves the heat transmission.

The entire apparatus is accommodated in an insulated casing 17, which also contains a cooling battery 18, to which the suction side of the fan 16 is connected.

As indicated by dashed lines in the drawing, a second foil strip 19 can be passed essentially parallel with the supporting belt 7 and the foil strip 11 from a storage roll 20 to a receiving roll 21. By means of resiliently suspended deflecting rollers 22 and 23, the second foil strip 19 can be made to follow a path which connects to the top faces of the food products 6 conveyed on the foil strip 11 and the supporting belt 7 along the upper run 12.

The foil strip 19 is also pressed down towards the top face of the food products 6 by means of jets of cold air, which are directed by the nozzles 24 towards the upper side of the second foil strip 19. Like the nozzles 14, nozzles 24 constitute outlets from a duct 25, which can be connected to the outlet side of the fan 16 or to the outlet side of a correspondingly arranged fan, such that the jets of cold air from the nozzles 24 press the second foil strip 19 into good contact with at least an essential part of the top faces of the products 6 and, thus, rapidly freeze the surface layer closest to the foil strip 19.

In the above embodiment of the apparatus according to the invention, the supporting belt 7 and the foil strip 11 constitute a non-foraminous conveyor belt, which supports the food products 6 and towards the underside of which in the upper run 12 the jets of cold air are blown from the nozzles 14. In an alternative embodiment, a non-foraminous belt of metal or some other material could replace the belt 7 and the strip 11 and on its own constitute the non-foraminous conveyor belt.

In the above embodiment of the inventive apparatus, the foil strip 19 forms in the same manner a non-foraminous cover belt, which in an alternative embodiment could be a belt of metal or some other material having good thermal conductivity.

## CLAIMS

1. A method of freezing a surface layer of a food  
5 product (6), characterised in that the food  
product (6) is placed on a non-foraminous conveyor belt  
(7, 11), and that cold air in the form of jets is blown  
towards the underside of the non-foraminous conveyor  
belt.

10 2. A method as claimed in claim 1, characterised  
in that the cold air in the form of said  
jets is blown towards the underside of the non-foraminous  
conveyor belt (7, 11) in a stationary area, which extends  
over the width of the non-foraminous conveyor belt, and  
15 that the non-foraminous conveyor belt is successively  
moved past the stationary area.

3. A method as claimed in claim 1 or 2, characterised  
in that a superposed, non-foraminous  
cover belt (19), which is positioned above the non-fora-  
20 minous conveyor belt (7, 11), is moved in parallel there-  
with, and that cold air in the form of jets is blown  
towards the upper side of the superposed, non-foraminous  
cover belt.

4. An apparatus for freezing a surface layer of a  
25 food product (6), characterised by a non-  
foraminous conveyor belt (7, 11) and a plurality of sta-  
tionary nozzles (14) for blowing cold air in the form of  
jets towards the underside of the non-foraminous conveyor  
belt in an area which extends over the width of the non-  
30 foraminous conveyor belt.

5. An apparatus as claimed in claim 4, characterised  
in that the non-foraminous conveyor  
belt (7, 11) comprises a non-foraminous foil strip (11)  
supported by a foraminous supporting belt (7).

35 6. An apparatus as claimed in claim 4, characterised  
in that the non-foraminous conveyor




belt is a single non-foraminous belt of metal or some other material having good thermal conductivity.

7. An apparatus as claimed in any one of claims 4-6, characterised by a superposed, non-foraminous cover belt (19), which is arranged above the non-foraminous conveyor belt (7, 11) to cover a food product (6) positioned on said conveyor belt, and a plurality of additional stationary nozzles (24) for blowing cold air in the form of jets towards the upper side of the superposed, non-foraminous cover belt.

8. An apparatus as claimed in claim 7, characterised in that the superposed, non-foraminous cover belt (19) is a non-foraminous foil strip.

9. An apparatus as claimed in claim 7, characterised in that the superposed, non-foraminous cover belt is a belt of metal or some other material having good thermal conductivity.

10. An apparatus as claimed in any one of claims 4-10, characterised in that it constitutes a prefreezer (5) for a freezer (1) for complete freezing of the food product (6).



**SUBSTITUTE SHEET (RULE 26)**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/00735

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F25D 13/06, A23L 3/36

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F25D, A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5551251 A (OCHS ET AL), 3 Sept 1996 (03.09.96), column 2, line 58 - column 3, line 35, figures 1,2 --	1-10
A	GB 1595552 A (FRIGOSCANDIA CONTRACTING AB), 12 August 1981 (12.08.81), page 2, line 3 - line 80, figures 1-3 --	1-10
A	GB 2141813 A (STAR REFRIGERATION LIMITED (UNITED KINGDOM)), 3 January 1985 (03.01.85) --	1-10
A	US 5543167 A (ONODERA), 6 August 1996 (06.08.96) -- -----	1-10



Further documents are listed in the continuation of Box C.



See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

11 August 1998

Date of mailing of the international search report

17-08-1998

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Inger Löfving

Telephone No. +46 8 782 25 00

# INTERNATIONAL SEARCH REPORT

Information on patent family members

27/07/98

International application No.

PCT/SE 98/00735

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	5551251	A	03/09/96	WO 9743588 A AU 5856396 A	20/11/97 05/12/97
GB	1595552	A	12/08/81	CA 1070131 A DE 2805131 A,C FR 2380744 A JP 1366954 C JP 53103260 A SE 424802 B,C SE 7701856 A US 4204006 A	22/01/80 24/08/78 15/09/78 26/02/87 08/09/78 16/08/82 18/08/78 20/05/80
GB	2141813	A	03/01/85	NONE	
US	5543167	A	06/08/96	NONE	